


# CMI-MMPB322714-141



## Picture




## Features

- ▶ High current
- ▶ Low profile
- ▶ Low magnetic loss
- ▶ RoHS compliant

## Applications

- ▶ Audio AMP, TV SMPS, Slim Adapter, AV equipment, digital consumer electronics

## Dimension (Unit:mm)



A	B	C	D
33.0 Max.	31.0 Max.	14.0 Max.	27.3±0.5
E	G	I1	I2
25±0.5	3.6±0.3	0.8±0.1	0.9±0.2

## Schematic Diagram



## Specifications

Part No.	Inductance ( $\mu$ H) $\pm$ 7%	DCR (m $\Omega$ ) Max.	Saturation Current(A)		Test Frequency (Hz)
			25 °c	100 °c	
CMI-MMPB322714-141	140	192	15.5	13.5	100k

- Saturation Current : Depends on inductance saturation.  
(Inductance reduction from initial shall be under 20%)
- Test Condition : Temperature 20 °c  $\pm$  5 °c, Humidity 65%  $\pm$  20

Ilsan Sales Office (KOREA) +82)31-904-1444  
 Shenzhen Sales Office (CHINA) +86)755-8663-6929  
 Hungary Sales office (EUROPE) +36)30-913-7706

H.K Sales Office (HONGKONG) +852)2711-5551  
 LA Sales Office (USA) +1)866-446-3586

• You can also contact us by e-mail : [coilmaster@coilmaster.com](mailto:coilmaster@coilmaster.com)

- All specifications are subject to change without notice.
- Update date : 2018.11.26

[www.coilmaster.com](http://www.coilmaster.com)